


# S270

## 277/480 VAC




**K** UL 1077 CSA C22.2 - NO. 235  
 VDE 0641 IEC-898  
 Cable & equipment protection

Rated current	Catalog number	Wgt. oz. (1 pc.)	Rated current	Catalog number	Wgt. oz. (1 pc.)
0.5	S271-K0.5	4.5	0.5	S273-K0.5	13.5
1	S271-K1		1	S273-K1	
1.6	S271-K1.6		1.6	S273-K1.6	
2	S271-K2		2	S273-K2	
3	S271-K3		3	S273-K3	
4	S271-K4		4	S273-K4	
5	S271-KS5		5	S273-KS5	
6	S271-K6		6	S273-K6	
8	S271-K8		8	S273-K8	
10	S271-K10		10	S273-K10	
13	S271-K13		13	S273-K13	
15	S271-KS15		15	S273-KS15	
16	S271-K16		16	S273-K16	
20	S271-K20		20	S273-K20	
25	S271-K25		25	S273-K25	
30	S271-KS30	30	S273-KS30		
32	S271-K32	32	S273-K32		
40	S271-K40	40	S273-K40		
50	S271-K50	50	S273-K50		
60	S271-KS60	60	S273-KS60		
63	S271-K63	63	S273-K63		
0.5	S271-K0.5NA	9.0	0.5	S273-K0.5NA	18.0
1	S271-K1NA		1	S273-K1NA	
1.6	S271-K1.6NA		1.6	S273-K1.6NA	
2	S271-K2NA		2	S273-K2NA	
3	S271-K3NA		3	S273-K3NA	
4	S271-K4NA		4	S273-K4NA	
6	S271-K6NA		6	S273-K6NA	
8	S271-K8NA		8	S273-K8NA	
10	S271-K10NA		10	S273-K10NA	
13	S271-K13NA		13	S273-K13NA	
16	S271-K16NA		16	S273-K16NA	
20	S271-K20NA		20	S273-K20NA	
25	S271-K25NA		25	S273-K25NA	
32	S271-K32NA		32	S273-K32NA	
40	S271-K40NA		40	S273-K40NA	
50	S271-K50NA	50	S273-K50NA		
63	S271-K63NA	63	S273-K63NA		
0.5	S272-K0.5	9.0	0.5	S274-K0.5	18.0
1	S272-K1		1	S274-K1	
1.6	S272-K1.6		1.6	S274-K1.6	
2	S272-K2		2	S274-K2	
3	S272-K3		3	S274-K3	
4	S272-K4		4	S274-K4	
5	S272-KS5		5	S274-K5	
6	S272-K6		6	S274-K6	
8	S272-K8		8	S274-K8	
10	S272-K10		10	S274-K10	
13	S272-K13		13	S274-K13	
15	S272-KS15		15	S274-K15	
16	S272-K16		16	S274-K16	
20	S272-K20		20	S274-K20	
25	S272-K25		25	S274-K25	
30	S272-KS30	30	S274-K30		
32	S272-K32	32	S274-K32		
40	S272-K40	40	S274-K40		
50	S272-K50	50	S274-K50		
60	S272-KS60	60	S274-K60		
63	S272-K63	63	S274-K63		

**Pro M**

### Switched neutral

To create a miniature circuit breaker from stock items with a switched neutral, order standard MCB (usually a single or three pole version) and a neutral disconnect module, S2-NT, which can be field added to the MCB.



# S280 277/480 VAC

**K** UL 1077 CSA C22.2 - NO. 235  
VDE 0660  
Cable & equipment protection



S281-K16



S282-K1



S283-K63

Rated current	Catalog number	Wgt. oz. (1 pc.)	Rated current	Catalog number	Wgt. oz. (1 pc.)
0.2	S281-K0.2	4.6	0.2	S283-K0.2	13.9
0.3	S281-K0.3		0.3	S283-K0.3	
0.5	S281-K0.5		0.5	S283-K0.5	
0.75	S281-K0.75		0.75	S283-K0.75	
1	S281-K1		1	S283-K1	
1.6	S281-K1.6		1.6	S283-K1.6	
2	S281-K2		2	S283-K2	
3	S281-K3		3	S283-K3	
4	S281-K4		4	S283-K4	
6	S281-K6		6	S283-K6	
8	S281-K8		8	S283-K8	
10	S281-K10		10	S283-K10	
13	S281-K13		13	S283-K13	
16	S281-K16		16	S283-K16	
20	S281-K20		20	S283-K20	
25	S281-K25		25	S283-K25	
32	S281-K32	32	S283-K32		
40	S281-K40	40	S283-K40		
50	S281-K50	50	S283-K50		
63	S281-K63	63	S283-K63		
0.2	S282-K0.2	9.2	0.2	S282-K0.2	
0.3	S282-K0.3		0.3	S282-K0.3	
0.5	S282-K0.5		0.5	S282-K0.5	
0.75	S282-K0.75		0.75	S282-K0.75	
1	S282-K1		1	S282-K1	
1.6	S282-K1.6		1.6	S282-K1.6	
2	S282-K2		2	S282-K2	
3	S282-K3		3	S282-K3	
4	S282-K4		4	S282-K4	
6	S282-K6		6	S282-K6	
8	S282-K8		8	S282-K8	
10	S282-K10		10	S282-K10	
13	S282-K13		13	S282-K13	
16	S282-K16		16	S282-K16	
20	S282-K20		20	S282-K20	
25	S282-K25		25	S282-K25	
32	S282-K32	32	S282-K32		
40	S282-K40	40	S282-K40		
50	S282-K50	50	S282-K50		
63	S282-K63	63	S282-K63		

### Switched neutral

To create a miniature circuit breaker from stock items with a switched neutral, order standard MCB (usually a single or three pole version) and a neutral disconnect module, S2-NT, which can be field added to the MCB.

