


# POLYPROPYLENE INSULATED END SLEEVES

for flexible Copper cables

**PKE**  
**PKC**  
**CPKD**



The PKE, PKC, CPKD range of end sleeves is manufactured from Tin plated electrolytic Copper. Designed and developed to reinforce fine wire strands when terminating a cable into a connector block.

The operating temperature range is - 20 to + 105°C (Surge + 110°C).

Recommended crimping tools are shown on pages 98 to 122, 125, 152, 154, 156.



**VALSTAR ND#2/PKE**  
Comprising:  
- a selection of PKE end sleeves conductor size 1+6 sqmm  
- tool ND#2

**VALSTAR ND#2/PKC**  
Comprising:  
- a selection of PKC end sleeves conductor size 1+6 sqmm  
- tool ND#2

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1+0,3	PKE 308	1,9	1,1	8,0	12,4	yellow	25.000/500
0,3+0,5	PKE 508	2,6	1,3	8,0	14,0	white	10.000/500
0,75	PKE 7508	3,4	1,6	8,2	14,6	blue	10.000/500
1,0	PKE 108	3,4	1,8	8,2	14,6	red	10.000/500
1,5	PKE 1508	3,8	2,1	8,2	14,6	black	10.000/500
	PKE 1518	3,8	2,1	18,0	24,4		5.000/500
2,5	PKE 2508	4,4	2,6	8,2	15,2	grey	7.500/500
	PKE 2518	4,4	2,6	18,0	25,0		5.000/500
4,0	PKE 408	4,8	3,2	9,0	16,0	orange	5.000/200
	PKE 418	4,8	3,2	18,0	25,0		3.000/200
6,0	PKE 612	5,8	3,9	12,0	20,0	green	2.500/100
	PKE 618	5,8	3,9	18,0	26,0		2.000/100
10,0	PKE 1012	7,4	4,8	12,0	21,5	brown	1.500/100
	PKE 1018	7,4	4,8	18,0	27,5		1.500/100
16,0	PKE 1612	9,3	5,9	12,0	22,7	white	1.000/100
	PKE 1618	9,3	5,9	18,0	28,6		1.000/100
25,0	PKE 25016	10,0	7,9	16,0	29,0	black	500/50
	PKE 25022	10,0	7,9	22,0	35,0		500/50



## Insulated chain end sleeves

Developed for use with production equipment to give a quick and reliable crimped joint. Conforms to DIN standard 46 228/4.

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Reel
		Ø	B	P	L		
0,3+0,5	CPKD 508	2,6	1,3	8,0	14,0	white	5.000
0,75	CPKD 7508	2,8	1,5	8,0	14,0	grey	5.000
1	CPKD 108	3,0	1,7	8,0	14,0	red	5.000
1,5	CPKD 1508	3,5	2,0	8,0	14,0	black	5.000
2,5	CPKD 2508	4,2	2,5	8,0	14,0	blue	3.000

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1+0,3	PKC 306	1,9	1,1	6,0	10,4	light blue	25.000/500
	PKC 308	1,9	1,1	8,0	12,4		25.000/500
0,3+0,5	PKC 508	2,6	1,3	8,0	14,0	orange	10.000/500
	PKC 510	2,6	1,3	10,0	16,0		10.000/500
0,75	PKC 7508	3,4	1,6	8,2	14,6	white	10.000/500
	PKC 7512	3,4	1,6	12,0	18,4		10.000/500
1,0	PKC 108	3,4	1,8	8,2	14,6	yellow	10.000/500
	PKC 112	3,4	1,8	12,0	18,4		10.000/500
1,5	PKC 1508	3,8	2,1	8,2	14,6	red	10.000/500
	PKC 1518	3,8	2,1	18,0	24,4		5.000/500
2,5	PKC 2508	3,9	2,6	8,2	15,2	blue	7.500/500
	PKC 2518	3,9	2,6	18,0	25,0		5.000/500
4,0	PKC 408	4,8	3,2	9,0	16,0	grey	5.000/200
	PKC 418	4,8	3,2	18,0	25,0		3.000/200
6,0	PKC 612	5,8	3,9	12,0	20,0	black	2.500/100
	PKC 618	5,8	3,9	18,0	26,0		2.000/100
10,0	PKC 1012	7,4	4,8	12,0	21,5	ivory	1.500/100
	PKC 1018	7,4	4,8	18,0	27,5		1.500/100
16,0	PKC 1612	9,3	5,9	12,0	22,7	green	1.000/100
	PKC 1618	9,3	5,9	18,0	28,6		1.000/100
25,0	PKC 25016	10,0	7,9	16,0	29,0	brown	500/50
	PKC 25022	10,0	7,9	22,0	35,0		500/50
35,0	PKC 35016	12,0	8,9	16,0	30,0	beige	500/50
	PKC 35025	12,0	8,9	25,0	39,0		400/50
50,0	PKC 50020	13,8	11,0	20,0	36,0	olive	300/50
	PKC 50030	13,8	11,0	30,0	46,0		250/50
70	PKC 70022	16,0	14,3	22,0	38,0	yellow	100/25
95	PKC 95025	18,0	15,7	25,0	44,0	red	100/25
120	PKC 120027	21,0	17,5	27,0	48,0	blue	100/25