

# RF-F BF-F GF-F



- Manufactured from Brass strip
- Electrolytically Tin plated
  - The operating temperature range is -20 to +115°C (Surge +130°C).
  - Recommended crimping tools are shown on pages 98 to 117, 152

## FEMALE DISCONNECT TERMINALS

Certified according to  
**EN 45545-2:2013**



### Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F 305	2,8 x 0,5	3.000/100
	RF-F 308*	2,8 x 0,8	3.000/100
	RF-F 405	4,8 x 0,5	2.500/100
	RF-F 408	4,8 x 0,8	2.500/100
1,5÷2,5 (16÷14)	BF-F 405	4,8 x 0,5	2.500/100
	BF-F 408	4,8 x 0,8	2.500/100
	BF-F 608	6,35 x 0,8	1.500/100
4÷6 (12÷10)	GF-F 608	6,35 x 0,8	1.000/100

### Polycarbonate fully insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F 305P	2,8 x 0,5	2.000/100
	RF-F 308P*	2,8 x 0,8	2.000/100
	RF-F 405P	4,8 x 0,5	1.500/100
	RF-F 408P	4,8 x 0,8	1.500/100
1,5÷2,5 (16÷14)	BF-F 608P	6,35 x 0,8	1.000/100
	BF-F 405P	4,8 x 0,5	1.500/100
	BF-F 408P	4,8 x 0,8	1.500/100
4÷6 (12÷10)	GF-F 608P	6,35 x 0,8	800/100

\*Not UL approved

# RF-M BF-M GF-M



- Manufactured from Brass strip
- Electrolytically Tin plated
  - The operating temperature range is -20 to +115°C (Surge +130°C).
  - Recommended crimping tools are shown on pages 98 to 117, 152

## MALE DISCONNECT TERMINALS

Certified according to  
**EN 45545-2:2013**



### Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M 608	6,35 x 0,8	3.000/100
1,5÷2,5 (16÷14)	BF-M 608	6,35 x 0,8	2.000/100
4÷6 (12÷10)	GF-M 608	6,35 x 0,8	1.000/100

### Polycarbonate fully insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M 608P	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-M 608P	6,35 x 0,8	1.000/100

# RF-FM BF-FM RF-B BF-B



- Manufactured from Brass strip
- Electrolytically Tin plated
  - The operating temperature range is -20 to +115°C (Surge +130°C).
  - Recommended crimping tools are shown on pages 98 to 117, 152

## MALE/FEMALE CONNECTORS

Certified according to  
**EN 45545-2:2013**



### Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Tab Size	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-FM 608	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-FM 608	6,35 x 0,8	1.000/100

## BULLET AND SOCKET CONNECTORS

### Polycarbonate insulated terminals - partially reinforced with Copper sleeve

Cond. Size sqmm (AWG)	Ref.	Ø mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-BM 4*	4	2.500/100
	RF-BF 4*	4	800/100
1,5÷2,5 (16÷14)	BF-BM 5*	5	2.000/100
	BF-BF 5*	5	800/100

\*Not UL approved