

SLIP ID.	MASTER	WORKING CLASSIFICATION		≠=NTL. INSP	≠=RGLTR INSP SPARE	≠=DISPATCH FORM
400	DWG. NO.	カ=FABRICATION	M:NTL. INSP. LIST	S:STANDARD PT	T:SINGLE PT	
	M: MACH. BF. WELD B: OTHER ORDER T: APPND. DWG	キ=MACHINING	S: ULTRA SONIC INSP	R: RECOMMENDED PT	K: ASSY. UNIT	
	P: SEPARATE PL. Z: NTL. FINISHED ORDERING	ク=ASSEMBLY	U: M+S	P: PERIODIC PT	X: SINGLE PT AF ASSY.	
	^{3B} DESCRIPTION-NOMINAL DIMENSION	⁴ PART	^{5B} MATERIAL-DIMENSIONS	⁶ APPOINTED SYMBOLS	⁵ MASS	⁷ OTHER ITEM NO.
	DRAWING NO. - STANDARD NO.	NTL. MASS	OR PATTERN NO.	OR INDICATING SYMBOLS	NTL. CBT	力キ力機定出実
PIECES						
MTL PIECES						
C						
4	PACKING, CL-B	31	RUBBER1-3060, 6*D24/D15	<M673-259165C2P9>		
4	SPRING WASHER, M10	32	STEEL JIS	<M673-259165C2P12>		
4	INS. WASHER, M10	33	SLMP FS856-26	<M673-259165C2P13>		
4	INS. TUBE	34	EP-P FS856-25	<M673-259165C2P14>		
4	CLOW WASHER, M8	35	STEEL JEM	<M673-259165C2P16>		
2	PACKING	36	ALUMINIUM, 2*D22/D13	<M673-259165C2P18>		
1	SEAL	37	THREE BOND, 1121*1KG	<M673-259165C2P19>		
6	CLAW WASHER, M30	39	STEEL JEM	<M605-258721P18>		
2	O RUBBER, 3*1000	40	CL-A KRS18-506	<M605-258721P29>		
2	LINERS<COMB.>	41	M030-4D0960 C1	<M605-258721P31>		
1	LINERS<COMB.>	42	M030-4D0960 C2	<M605-258721P32>		
6	CLAW WASHER, M30	44	STEEL JEM	<M605-258722P18>		
2	INS. TAPPER PIN	45	<30X140> M042-525388D	<M605-258722P26>		

REVISIONS			DWG. CODE	
			TITLE	CONSUMABLE PARTS LIST FOR MAINTENANCE
	DRAWN	K. WADA	APPROVED	
CHECKED	K. ISHIDA		SCALE	
DATE	1998-02-27			
Fuji Electric Co., Ltd.		REF.	DRAWING NO.	M798 . <4/23> 899158

4

5

6