


SPRINT EMC railway cable glands with earthing cones DIN 89345, EMSKV EMV-Z RW, brass nickel-plated, metric, EN 45545



EMSKV EMV-Z RW



Protection class IP68 (5 bar 30 min) / IP69
Temperature range -40 °C - 100 °C
Hazard level EN acc. 45545 R22=HL3 / R23=HL3
Material Gland Brass nickel-plated, Clamping cage Polyamide UL94-V0, Earthing cones Brass chromium-plated, Gasket EPDM

Type	WISKA-No. Ni					TL (mm)	
EMSKV 12 EMV-Z RW	10104303	M 12x1,5	5	3 · 7	16	23 · 30	50
EMSKV 16 EMV-Z RW	10104304	M 16x1,5	5	4,5 · 10	20	26 · 34	50
EMSKV 20 EMV-Z RW	10104305	M 20x1,5	6	6 · 13	24	29 · 37	50
EMSKV 25 EMV-Z RW	10104306	M 25x1,5	7	9 · 17	29	33 · 42	50
EMSKV 32 EMV-Z RW	10104307	M 32x1,5	8	13 · 21	36	36 · 44	25
EMSKV 50 EMV-Z RW	10104308	M 50x1,5	9	21 · 35	55	51 · 62	10
EMSKV 40 EMV-Z RW	10104309	M 40x1,5	8	16 · 28	46	44 · 55	10
EMSKV 63 EMV-Z RW	10104310	M 63x1,5	10	34 · 48	68	56 · 67	10
EMSKV 75 EMV-Z RW	10104311	M 75x1,5	12	48 · 63	82	67 · 81	1

Recommended accessories



CABLE GLANDS
 POLYAMIDE METALLIC
 MARITIME
 EMC
 EX E/I
 EX D
 RAILWAY
 VENTING
 BRITISH STANDARD
 SEALINGS
 MEMBRANE CABLE ENTRIES
 GROMMETS
 CABLE ENTRY SYSTEM
 CONMAXX
 CONMAXX GLAND
 CABLE PROTECTION
 BRACE FITTING NON-METALLIC
 BRACE CONDUIT NON-METALLIC
 BRACE FITTING METALLIC
 BRACE CONDUIT METALLIC
 BRACE SLEEVE