

GD2534 VACUUM PUMP (OIL-LESS)



- Economical
- Oil Free
- Adjustable Vacuum / Pressure
- Aspiration
- Vacuum Filtration

Reliable WOB-L Piston pumps are perfect for many common laboratory vacuum applications.

Features:

- Vacuum and Pressure - to 70 Torr (27.2"Hg).
- Includes Vacuum and Pressure Regulators and Gauges simple to adjust and monitor vacuum level and delivery pressure.
- Inlet Water Trap - float ball rises to seal off pump from accidental ingestion of water
- Muffler quiets pump and filters discharge air.
- For use with dry or aqueous vapor applications only.

Specifications

Application	Filtration (1 to 4 funnels), Aspiration, Desiccation, SPE, Replace water aspirator, Vacuum Drying
Type	Laboratory Vacuum Pump
Free Air Displacement cfm (l/min.) @60Hz	1.2(34)
Free Air Displacement cfm (l/min.) @50Hz	1.7 (28)
Ultimate Pressure	70(93)
Maximum Vacuum	27.2" Hg
Max Pressure PSIG (pascal)	50(5 x 105)
Motor	1/8 HP (93 Watts)
Tubing needed	5 mm
Overall Dimensions	20.6 x 22.4 x 25.4 cm