

# Welded Centralizers *continued*

Welded Centralizer Size Chart

Hole Size (inches)	Casing Size (inches)												
	2-3/8	2-7/8	3-1/2	4-1/2	5	5-1/2	6-5/8	7	7-5/8	8-5/8	9-5/8	10-3/4	
4-1/2 to 4-3/4	•	•	•										
5-3/4 to 6	•	•	•	•	•								
6-1/8 to 6-3/8	•	•	•	•	•								
6-1/2 to 6-3/4	•	•	•	•	•	•							
7-3/8 to 7-7/8	•	•	•	•	•	•	•						
8-3/8 to 8-5/8	•	•	•	•	•	•	•	•	•				
8-3/4 to 9	•	•	•	•	•	•	•	•	•				
9-1/2 to 10	•	•	•	•	•	•	•	•	•				
10-5/8 to 11		•	•	•	•	•	•	•	•	•			
12 to 12-1/4			•	•	•	•	•	•	•	•	•		•
14 to 15-1/2					•	•	•	•	•	•	•		•
17 to 18-5/8											•	•	•
19-1/2 to 20-1/2													
22 to 23													
24 to 26													
26 to 28													
28 to 30													
30 to 32													
32 to 34													
34 to 36													
> 36													

Note: Several options may exist for each hole size combination. Please consult your Weatherford technical specialist for application recommendations.

**Welded Centralizer Size Chart** *continued*

Hole Size (inches)	Casing Size (inches)											
	11-3/4	13-3/8	16	18-5/8	20	22	24	26	28	30	32	36
4-1/2 to 4-3/4												
5-3/4 to 6												
6-1/8 to 6-3/8												
6-1/2 to 6-3/4												
7-3/8 to 7-7/8												
8-3/8 to 8-5/8												
8-3/4 to 9												
9-1/2 to 10												
10-5/8 to 11												
12 to 12-1/4												
14 to 15-1/2	•	•										
17 to 18-5/8	•	•	•									
19-1/2 to 20-1/2			•									
22 to 23			•	•	•							
24 to 26				•	•	•						
26 to 28				•	•	•	•					
28 to 30						•	•	•				
30 to 32							•	•	•			
32 to 34							•	•	•	•		
34 to 36									•	•	•	
> 36											•	•

Note: Several options may exist for each hole size combination. Please consult your Weatherford technical specialist for application recommendations.

**Options**

- End collars are available in latch-on or slip-on configurations.
- Custom designs are available for nonstandard applications.
- The S-series centralizer meets or exceeds API Specification 10D.
- The B-series centralizer offers an economic solution for wells that do not require the performance capabilities of the S-series centralizers.