

**LF777**

Lube, By-Pass Spin-On

[Add To Worksheet](#)

Note: All parts are not available in all regions of the world. Contact your [Customer Assistance Center](#) (<https://www.cumminsfiltration.com/customerassistance>) to ensure availability.

[Export As...](#)

[Click On The Image For Larger View](#)

Attributes	
Overall Height	249.2 mm (9.811 in)
Largest OD	116.08 mm (4.57 in)
Seam OD	116.08 mm (4.57 in)
Gasket OD	111.38 mm (4.385 in)
GASKET INSIDE DIAMETER	103.17 mm (4.062 in)
Thread Size	1 3/8-16 UNS-2B
Standpipe	NO
30 MICRON EFFICIENCY, TWA	99 % (99 %)
Primary Applications	
CUMMINS	<a href="#">3889311 (/catalog/CatalogSearch.do?reqCmd=PartInformation&amp;partNumber=3304173S&amp;partflag1=5&amp;forPartNumber=LF777&amp;criteria=partNumber_PartDeatils=3889311)</a>
Product Comments	
<ul style="list-style-type: none"> <li>2.0 GPM flow rates</li> </ul>	
Filter Used With	
<a href="#">3304173S (/catalog/partsearch.do?reqCmd=PartInformation&amp;partNumber=3304173S&amp;partflag1=5&amp;forPartNumber=LF777&amp;criteria=partNumber_PartDeatils=3304173S)</a> Adaptor head, remote mount	



◆ 2018 Cummins Filtration

[PRIVACY POLICY \(HTTPS://WWW.CUMMINSFILTRATION.COM/PRIVACY\)](https://www.cumminsfiltration.com/privacy) | 
 [TERMS AND CONDITIONS \(HTTPS://WWW.CUMMINSFILTRATION.COM/TERMS-AND-CONDITIONS\)](https://www.cumminsfiltration.com/terms-and-conditions) | 
 [COOKIES \(HTTPS://WWW.CUMMINSFILTRATION.COM/COOKIES\)](https://www.cumminsfiltration.com/cookies) | 
 [SITE MAP \(HTTPS://WWW.CUMMINSFILTRATION.COM/SITEMAP\)](https://www.cumminsfiltration.com/sitemap)