

# Miniature Circuit Breaker (MCB)

NC45H

DIT

1

## IEC 60947-2 : 10 kA

Untuk pemakaian di bangunan komersial dan industri, ketika tingkat arus hubung singkat tidak melebihi 10 kA

- Kapasitas pemutusan berdasarkan standar IEC 60947-2, Icu = 10 kA
- Kurva C (magnetis trip antara 7 dan 10 In)



12095

1 kutub



Kutub	Pengenal (A)	Referensi	Harga (Rp)	SS	Lot
1 kutub	1	12092	126,500	0	12
	2	12093	126,500	0	12
	3	12094	126,500	0	12
	6	12095	126,500	0	12
	10	12096	126,500	0	12
	16	12097	126,500	0	12
	20	12098	126,500	0	12
	25	12099	141,500	0	12
	32	12100	148,500	0	12
	40	12101	158,500	0	12
2 kutub	1	12102	309,500	2	6
	2	12103	309,500	1	6
	3	12104	309,500	1	6
	6	12105	309,500	1	6
	10	12106	309,500	1	6
	16	12107	309,500	1	6
	20	12108	309,500	1	
	25	12109	324,000	1	
	32	12110	331,500	2	6
	40	12111	343,000	2	6
3 kutub	1	12112	447,000	2	
	2	12113	447,000	1	4
	3	12114	447,000	1	4
	6	12115	447,000	0	4
	10	12116	447,000	0	4
	16	12117	447,000	0	4
	20	12118	447,000	0	4
	25	12119	461,000	0	4
	32	12120	468,500	0	4
	40	12121	479,000	0	4




12105

2 kutub



12117

3 kutub



**Catatan :**

Alat bantu listrik dan perlengkapan NC45H, lihat halaman : 1-13