

The GE Lucalox range

Watts	CCT °K	Max. Overall Length mm	Diameter mm	LCL mm	Order Code	CRI Ra	Lumen Maint.	Cap	Operating Position	Initial Lumens	Rated Average Life Hours	Pack Qty	Product Code
Lucalox® T Tubular Clear - Amalgam Reservoir										⚠			
50	2000	156	38.5	97	LU50/90/T/27	25	80	E27	U	3400	28500	25	22445
70	2000	156	38.5	97	LU70/90/T12/27	25	80	E27	U	6000	28500	25	22452
100	2000	211	48	133	LU100/100/T/40	25	80	E40	U	9600	28500	12	17590
150	2000	211	48	133	LU150/100/T/40	25	80	E40	U	15000	28500	12	44244
250	2000	260	48	158	LU250/T/40	25	80	E40	U	27500	28500	12	22453
400	2000	278	48	175	LU400/T/40	25	80	E40	U	50000	28500	12	11678
1000*	2000	372	67	240	LU1000/110/T/40	25	80	E40	U	130000	24000	12	35045
Lucalox® D Diffuse Elliptical - Amalgam Reservoir										⚠			
50	2000	154	72	-	LU50/90/D/27	25	80	E27	U	3300	28500	12	10794
70	2000	154	72	-	LU70/90/D/27	25	80	E27	U	5800	28500	12	10101
100	2000	186	76	-	LU100/100/D/40	25	80	E40	U	9200	28500	12	17589
150	2000	227	91	-	LU150/100/D/40	25	80	E40	U	14500	28500	12	44245
250	2000	227	91	-	LU250/D/40	25	80	E40	U	26000	28500	12	44052
400	2000	292	122	-	LU400/D/40	25	80	E40	U	47500	28500	6	44057
1000*	2000	372	162	-	LU1000/110/D/40	25	80	E40	U	120000	24000	1	30228
Lucalox® HO - High Output Tubular Clear - Amalgam Reservoir										⚠			
50	2000	156	38.5	97	LU50/85/HO/T/27	25	90	E27	U	4000	28500	25	35109
70	2000	156	38.5	97	LU70/90/HO/T12/27	25	90	E27	U	6500	28500	25	35112
100	2000	211	48	133	LU100/100/HO/T/40	25	90	E40	U	10000	28500	12	35113
150	2000	211	48	133	LU150/100/HO/T/40	25	90	E40	U	17500	28500	12	35114
250	2000	260	48	158	LU250/HO/T/40	25	90	E40	U	33000	28500	12	35120
400	2000	278	48	175	LU400/HO/T/40 NG	25	90	E40	U	56500	28500	12	47963
600	2000	278	48	175	LU600/HO/T/40 NG	25	90	E40	U	90000	28500	12	47962
Lucalox® HO - High Output Diffuse Elliptical - Amalgam Reservoir										⚠			
100	2000	186	76	-	LU100/100/HO/D/40	25	90	E40	U	9600	28500	12	35300
150	2000	227	91	-	LU150/100/HO/D/40	25	90	E40	U	16900	28500	12	35301
250	2000	227	91	-	LU250/HO/D/40	25	90	E40	U	31200	28500	12	35302
400	2000	292	122	-	LU400/HO/D/40	25	90	E40	U	53700	28500	6	35295
Lucalox® RFL - Reflector										⚠			
70	2000	144	96	-	LU70/RFL	25	80	E27	U	4000	24000	10	30238
Lucalox® E-Z Lux® Mercury Retrofit - Diffuse Elliptical - Amalgam Reservoir										⚠			
110	2000	175	75	-	LUH110/D/EZ/27	25	84	E27	U	8800	10000	12	11683
215	2000	232	89	-	LUH215/D/EZ/40	25	90	E40	U	18000	12000	12	49941
Lucalox® I - Internal Ignitor Clear Elliptical, Amalgam Reservoir										⚠			
50	2000	156	72	117	LU50/90/I/27	25	85	E27	U	3400	12000	12	11733
70	2000	156	72	117	LU70/90/I/27	25	85	E27	U	6000	12000	12	11735
Lucalox® I - Internal Ignitor Diffuse Elliptical - Amalgam Reservoir										⚠			
50	2000	156	72	-	LU50/90/D/I/27	25	85	E27	U	3300	12000	12	11734
70	2000	156	72	-	LU70/90/D/I/27	25	85	E27	U	5800	12000	12	11736
Lucalox® Classique Tubular Clear										⚠			
150	2200	210	48	132	LU150/CL-DL/T/40	60	87	E40	U	12000	14000	10	34929
250	2200	260	48	158	LU250/CL-DL/T/40	60	87	E40	U	23000	14000	10	44761
400	2200	285	48	175	LU400/CL-DL/T/40	60	87	E40	U	38000	14000	10	44759
Lucalox® Classique Diffuse Elliptical										⚠			
150	2200	227	91	-	LU150/CL-DL/D/40	60	87	E40	U	11500	14000	10	34928
250	2200	227	91	-	LU250/CL-DL/D/40	60	87	E40	U	22000	14000	10	44762
400	2200	286	122	-	LU400/CL-DL/D/40	60	87	E40	U	36000	14000	10	44760
Lucalox® TD - Tubular Double-ended Clear										⚠			
250	2000	191	22	-	LU250/TD	25	82	RX7s	H (±20°)	26000	24000	10	30241
400	2000	256	22	-	LU400/TD	25	82	RX7s	H (±20°)	48000	24000	10	30244
1000	2000	334	22	-	LU1000/TD	25	82	RX7s	H (±20°)	137500	24000	10	30246
Lucalox® Superlife Tubular Clear - Amalgam Reservoir										⚠			
50	2000	156	38.5	97	LU50/90/SBY/T/27	25	80	E27	U	3400	40000	25	35585
70	2000	156	38.5	97	LU70/90/SBY/T12/27	25	80	E27	U	6000	40000	25	35593
100	2000	211	48	133	LU100/100/SBY/T/40	25	80	E40	U	9600	40000	12	35592
150	2000	211	48	133	LU150/100/SBY/T/40	25	80	E40	U	15000	50000	12	35594
250	2000	260	48	158	LU250/SBY/T/40	25	80	E40	U	27500	55000	12	35586
400	2000	278	48	175	LU400/SBY/T/40	25	80	E40	U	50000	55000	12	35582
Lucalox® Superlife Diffuse Elliptical - Amalgam Reservoir										⚠			
50	2000	156	72	-	LU50/90/SBY/D/27	25	80	E27	U	3300	40000	12	35583
70	2000	156	72	-	LU70/90/SBY/D/27	25	80	E27	U	5800	40000	12	35587
100	2000	186	76	-	LU100/100/SBY/D/40	25	80	E40	U	9200	40000	12	35588
150	2000	227	91	-	LU150/100/SBY/D/40	25	80	E40	U	14500	50000	12	35589
250	2000	227	91	-	LU250/SBY/D/40	25	80	E40	U	26000	55000	12	35590
400	2000	292	122	-	LU400/SBY/D/40	25	80	E40	U	47500	55000	6	35591

⚠ External Ignitor ⚠ Internal Ignitor

* Internal amalgam reservoir

Notes: Operating position universal except for TD Horizontal ±20° ANSI specification Lucalox lamps are available upon request
Please contact your local sales office for further information
GE reserve right to change specification