

## Data sheet for Output reactor

Article No. : 6SL3000-2BE32-1AA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :




Figure similar

### Rated data

|               |          |
|---------------|----------|
| Rated current | 210.00 A |
| Power loss    | 0.486 kW |

### Mechanical data

|                      |                   |
|----------------------|-------------------|
| Degree of protection | IP00              |
| Net weight           | 60 kg (132.28 lb) |

### Dimensions

|        |                   |
|--------|-------------------|
| Width  | 300 mm (11.81 in) |
| Height | 285 mm (11.22 in) |
| Depth  | 257 mm (10.12 in) |

### Connections

#### Power connection Power Module

|         |                                  |
|---------|----------------------------------|
| Version | flat connector for cable lug M10 |
|---------|----------------------------------|

#### Power connection motor

|         |                                     |
|---------|-------------------------------------|
| Version | Flange connection for cable lug M10 |
|---------|-------------------------------------|

#### Max. motor cable length

##### 3 AC 380 V -10 % ... 400 V

|            |       |
|------------|-------|
| Shielded   | 300 m |
| Unshielded | 450 m |

##### 3 AC 401 V ... 480 V +10 %

|            |       |
|------------|-------|
| Shielded   | 300 m |
| Unshielded | 450 m |

#### PE connection

|         |          |
|---------|----------|
| Version | M8 Screw |
|---------|----------|