

Product datasheet

Specifications



Fusarc CF, IND, 7.2 kV, 200 A, 292 mm

757352BQ

Main

Range Of Product	Fusarc CF
Quality Labels	ISO 14001 ISO 9001
Standards	IEC 60282-1 IEC 60787 DIN 43625 VDE 0670-402
Product Or Component Type	Fuse
Protection Technology	Current limiter Thermal limiter

Complementary

[In] Rated Current	200 A
Rated Voltage (Ur)	7.2 kV
[Ue] Rated Operational Voltage	3...7.2 kV
Maximum Discharge Current	50 kA
Braking Current	1400 A
Average Resistance	1.8 mOhm at 20 °C +/- 10 %
Power Dissipation In W	95 W
Type Of Installation	Indoor
Material	Glass fiber
Product Destination	Motor Power transformer Capacitor Voltage transformer
Condition Of Use	Cubicle In open air Fuse chamber
Length	292 mm
Net Weight	3.4 kg
Diameter	86 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.500 cm

Package 1 Width	9.500 cm
Package 1 Length	36.000 cm
Package 1 Weight	3.610 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	48
Package 2 Height	50.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	187.680 kg