



# Needle Valve, 5000 PSI - V Series | #8A-V8LN-SS [View Series Page](#)



## Local Contact

### Parker Hannifin Corporation

Instrumentation Products Division

1005 A Cleaner Way

Huntsville, AL 35805 USA

### Phone

+1 (256) 881-2040

### Fax

+1 (256) 881-5072

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

[Register now](#)

Parker's V Series Needle Valves are designed for positive leak tight shut-off and regulation of fluids and gases. These valves are for instrumentation and general purpose applications up to 5,000 PSI.

[Share / Email](#)

## Technical Specifications

**Body Type:**

Inline

**Stem Type:**

Needle

**Connection 2 Style:**

Two Ferrule Compression

**Connection 2 Size:**

1/2"

**Body Size (inch):**

1/2"

**Connection 1 Style:**

Two Ferrule Compression

**Body Material:**

316 Stainless Steel

**Connection 1 Size:**

1/2"

**Body Material:**

316 Stainless Steel

**Connection 1 Size:**

1/4"-1/2", Two Ferrule Compression, Single Ferrule Compression, NPT F, NPT M

**Connection 2 Size:**

1/4"-1/2", Two Ferrule Compression, Single Ferrule Compression, NPT F, NPT M

**Stem Type:**

Needle, Blunt, PCTFE

**Body Type:**

Inline

 **Safety Warning**

## Item Information

Parker's V Series Needle Valves are designed for positive, leak tight shut-off and regulation of fluids in process, power, and instrumentation applications. These inline and angle pattern valves come with a wide variety of port sizes and styles, temperature capabilities ranging from -65°F to 450°F (-54°C to 232°C) and pressures to 5000 psig (345 bar) ). V Series Needle Valves provide the utmost in flexibility when designing instrumentation tubing or piping systems.

Markets:

markets.

- Pulp and Paper

---

## CAD Drawings + Files

No CAD files available

---