







Model	Rated voltage (V)		Function	Sample and size	Mounting hole size
	ACDC	AC			
AD11-16/C-CDY	12、24 IF: ≤20mA		Intermittent, volume ≥80dB/10cm Color: red, yellow		M2.5 screw
AD11-16D/C-CDY			Intermittent, flash, volume ≥80dB/10cm Color: red, yellow		Mounting hole size: 16.2mm
AD11-16/D-CDY	12、24 IF: ≤20mA		Intermittent, volume ≥80dB/10cm Color: red, yellow		4.8 pin
AD11-16D/D-CDY			Intermittent, flash, volume ≥80dB/10cm Color: red, yellow		Mounting hole size: 16.2mm
AD11-22/21-CDY	12、24、48、110、220 IF: ≤20mA		Intermittent or continuous, Except 220V, volume ≥80dB/10cm Color: black		
AD11-22/21-CDY1			Intermittent or continuous, flash Except 220V, volume ≥80dB/10cm Color: red, green, yellow		
AD11-22D/21-CDY	12、24、48、110、220 IF: ≤20mA		Intermittent or continuous, flash Except 220V, volume ≥80dB/10cm Color: red, green, yellow		22.3mm or 25.5 (variable diameter of ring)
AD11-22D/21-CDY1			220 IF:20mA 380 IF:15mA		
AD11-22D/41-CDY		220 IF:20mA 380 IF:15mA	Intermittent or continuous, flash volume ≥80dB/10cm Color: red, green, yellow		
AD11-22D/41-CDY1			Intermittent or continuous, flash volume ≥80dB/10cm Color: red, green, yellow		
AD11-22D/21-CDYF	24、48、60 IF: ≤20mA		X1-X0: intermittent, X2-X0: flash. volume ≥80dB/10cm Color: red, green, yellow		
AD11-22D/21-CDYF1			X1-X0: continuous, X2-X0: flash. volume ≥80dB/10cm Color: red, green, yellow		