

↔		↔		⌚		⤴		⌘		⚖	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	21	0,83	10	150				0,320	0,215	
16	5/8	24	0,94	10	150				0,370	0,250	
19	3/4	27	1,06	10	150				0,420	0,280	
25	1	33	1,30	10	150				0,530	0,360	
32	1 1/4	42	1,65	10	150				0,820	0,550	
38	1 1/2	48	1,89	10	150				0,960	0,650	
51	2	61	2,40	10	150				1,270	0,850	
63	2 1/2	75	2,95	10	150				1,890	1,270	
76	3	88	3,46	10	150				2,270	1,530	
102	4	114	4,49	10	150				3,060	2,060	
115	4 1/2	127	5,00	10	150				3,400	2,280	
152	6	166	6,54	10	150				4,600	3,090	
203	8	219	8,62	10	150				6,820	4,580	

NA LA NEU CEU SA AP AU



254AA

Air-water delivery 10 bar (150 psi)

Tube: Black SBR
Reinforcement: High tensile textile cords
Cover: Black SBR - abrasion and ozone resistant
Use: Air and water delivery
Safety factor: 3:1 = 203mm 2:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

WATER & LIQUIDS

↔		↔		⌚		⤴		⌘		⚖	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
32	1 1/4	42	1,65	10	150				0,840	0,560	
35	1 3/8	45	1,77	10	150				0,910	0,610	
38	1 1/2	48	1,89	10	150				0,980	0,660	
40	1 9/16	50	1,97	10	150				1,030	0,690	
45	1 3/4	55	2,17	10	150				1,140	0,770	
51	2	61	2,40	10	150				1,300	0,870	
63	2 1/2	75	2,95	10	150				1,920	1,290	
76	3	88	3,46	10	150				2,300	1,550	
90	3 1/2	102	4,02	10	150				2,700	1,810	
102	4	114	4,49	10	150				3,100	2,080	

NA LA NEU CEU SA AP AU



254AH

Air-water delivery 10 bar (150 psi)

Tube: Black SBR
Reinforcement: High tensile textile cords
Cover: Red SBR - abrasion and ozone resistant
Use: Air and water delivery
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		⌚		⤴		⌘		⚖	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
51	2	61	2,40	18	270				1,070	0,720	
60	2 3/8	72	2,83	18	270				1,380	0,930	
70	2 3/4	82	3,23	18	270				1,600	1,080	
76	3	88	3,46	18	270				1,720	1,160	
80	3 1/8	92	3,62	18	270				1,870	1,260	
90	3 1/2	102	4,02	18	270				2,060	1,380	
102	4	114	4,49	18	270				2,350	1,580	
120	4 3/4	132	5,20	18	270				2,860	1,920	
152	6	168	6,61	18	270				4,880	3,280	

NA LA NEU CEU SA AP AU



256AA

Water-irrigation 18 bar (270 psi) - heavy duty

Tube: Black EPDM
Reinforcement: High tensile textile cords
Cover: Black EPDM - abrasion and ozone resistant
Use: Heavy duty water discharge.
 Specially designed for high pressure irrigation systems
Safety factor: 2,5:1 152 mm 2:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)