

Built-in components - Measuring Instrument AM 45/AM 72



Technical data

Ex-measuring instrument AM 45/AM 72	Moving iron	Moving coil
Marking accd. to 2014/34/EU	Ⓢ II 2 G Ex e II / D II 2 G Ex e mb II Ⓢ I M 2 Ex e I	Ⓢ II 2 G Ex ib IIC Ⓢ I M 2 Ex ib I
EC-Type Examination Certificate	PTB 99 ATEX 2032 U	
Application temperature	-20 °C up to +40 °C -55 °C up to +55 °C (option)	
Rated voltage	up to 420 V (AM 45) up to 750 V (AM 72)	
Power consumption (VA)	max. 0.31 A	
Overload range	10 fold - 25 sec. 25 fold - 4 sec. 50 fold - 1 sec. indicated 1 : 1.5, optional 1:6, 1:10	10 fold - 5 sec.
Measuring range	max. 0 - 25 A direct / n / 1A	0/4 - 24 mA
Inductance Li		< 0.1 mH
Capacitance Ci		< 0.1 nF
Winding specification of moving coil		26.5 windings
Internal resistance		2.5 Ω ±30 %
Open circuit voltage max. Ui		30 V
Connecting terminals max. Ii		150 mA
Accuracy	Class 2.5	Class 1.5
Movement	Moving iron	Moving coil
Connecting terminals	2 x 1.5 - 4 mm ²	
Degree of protection accd. to EN 60529	IP66 (installed condition)	
Display size	40 x 40 mm (AM 45) 68 x 68 mm (AM 72)	
Weight	0.35 kg	
Type of mounting	DIN rail mounting	
Enclosure material	Polycarbonate	

Built-in components - Measuring Instrument AM 45/AM 72

Ordering code for component (Code 2) Code A - C - D

Code	Component	Code
A	Measuring instrument AM 45	AM45
	Measuring instrument AM 72	AM72

Code	Movement	Code
C	Direct connection	1
	CT connection n/1 A	2
	CT connection n/5 A	3
	Power connection 0 - 20/24 mA (Scale 0-100% / 120%) ¹⁾	5
	Power connection 4 - 20/24 mA (Scale 0-100% / 120%) ¹⁾	6
	Moving-coil connection 0 - 20/24 mA (Scale 0-100% / 120%) ¹⁾³⁾	7
	Moving-coil connection 4 - 20/24 mA (Scale 0-100% / 120%) ¹⁾³⁾	8

Code	Measuring range	Code	Measuring range	Code
D	0 - 1	02	0 - 75 / 112.5 A	13
	0 - 2.5 / 3.75 A ²⁾	03	0 - 100 / 150 A	14
	0 - 5 / 7.5 A ²⁾	04	0 - 150 / 225 A	15
	0 - 10 / 15 A ²⁾	05	0 - 200 / 300 A	16
	0 - 15 / 22.5 A	06	0 - 250 / 375 A	17
	0 - 20 / 30 A ²⁾	08	0 - 300 / 450 A	18
	0 - 30 / 45 A	09	0 - 400 / 600 A	19
	0 - 40 / 60 A	10	0 - 500 / 750 A	20
	0 - 50 / 75 A	11	0 - 600 / 900 A	21
	0 - 60 / 90 A	12	0 - 100% / 150%	33

¹⁾ Movements 0 - 20 mA / 4 - 20 mA and with moving-coil connection are only available with scale 0 - 100 %/120 %v

²⁾ Version for direct connection or with CT connection n/1 A possible.

³⁾ Moving coil only for Ex-i or Ex-d flameproof applications - Other interchangeable scales available on request.

Example for ordering code (Code 2)

Movement	Measuring range	Ordering code		
		A	C	D
Measuring instrument AM 45				
Version with direct connection				
Direct (moving iron)	0 - 1 / 1.5 A	AM45	1	02
Direct (moving iron)	0 - 10 / 15 A	AM45	1	05
0 - 20 / 24 mA (moving coil)	0-100% / 120%	AM45	5	33
4 - 20 / 24 mA (moving coil)	0-100% / 120%	AM45	6	33
Moving iron measuring instrument AM 72				
Version with CT connection n/1A				
Converter n / 1A	0 - 100% / 150%	AM72	2	33
Moving-coil measuring instrument AM 45 (Ex-i application only)				
Version with direct connection				
0 - 20 / 24 mA	0-100% / 120%	AM45	7	33
4 - 20 / 24 mA	0-100% / 120%	AM45	8	33