



* SLIP : 2.7%
 * OIL QUANTITY : 23 Liter ("2"POINT)

CONV NO.	MOTOR POWER (kw)	SPEED (rpm)	INPUT SIDE			Q.TY (Set)
			D1	B1	H1	
	132	1480	+0.035 0	-0.022 -0.074	+0.2 0	2
			ø85	22	90.4	

MARK	DATE	REVISION	REASON	SIGNATURE

17	BOLT	M12x25	10.9	2	DACROTIZED
16	END PLATE	ø110x9	SS400	1	
15	KEY	25x14	S45C	1	JS B 130°
14	BOLT	M12x60	10.9	2	DACROTIZED
13	BOLT	M12x45	10.9	12	DACROTIZED
12	FLANGE	ø224x192.5	S45C	1	
11	PLUG	PT 3/8	PURCH.	1	
10	FUSIBLE PLUG	PT 3/8	PURCH.	1	
9	BEARING	#6216	PURCH.	1	
8	BEARING	#6026	PURCH.	1	
7	BEARING FLANGE	ø259x73	S45C	1	
6	BEARING CARRIER	ø261x38	S45C	1	
5	SHAFT	ø140x424	S45C-H	1	
4	CHAMBER	21CK	AL	1	
3	COVER	21K	AL	1	
2	OUTER	21K	AL	1	
1	INNER	21K	AL	1	

GENERAL TOLERANCES	SURFACE ROUGHNESS	FINISH
0.5-3	12.5	~
3-6	6.3	~
6-30	3.2	~
30-120	1.6	~
120-400	0.8	~
400-1000	0.4	~
1000-2000	0.2	~
2000-6000	0.1	~

NO.	DESCRIPTIONS	SIZE	MAT'L	QTY	WEIGHT (kg)	REMARKS
CUSTOMER		STANDARD	SCALE	1/4	PROJECTION	
TITLE		21 CKRDF-S FLUID COUPLING		DWG. NO.	CKRDF2100S	REV. NO. 7
DRAWN		CHECKED	APPROVED			
C.H. LEE	C.H. LEE	S.Y. KIM		NARA CORPORATION		
17.04.21	17.04.21	17.04.21				

3/3