

Type	Ordering Code	Watts (W)	Color Description	Color Temp. (K)	Color Type	Initial Lumens (lm)	Dimensions					Lamp Current (A)	Color Rendering Index (Ra)	Average Life (hours)	Std.Pkg Qty (inner)
							Length		Bulb Type	Tube Diameter (mm)	Base				
							In	mm							
Tripbospor															
Preheat Start Type	F20T9 EX-D	18	EX-D	6,700	867	1,350	24	589	T9	28	G13	0.360	84	8,500	25
	F20T9 EX-N	18	EX-N	5,000	850	1,470	24	589	T9	28	G13	0.360	84	8,500	25
	F20T9EX-L	18	EX-L	3,000	830	1,470	24	589	T9	28	G13	0.360	84	8,500	25
	F30T9/EX-D	30	EX-D	6,700	867	2,350	36	893	T9	28	G13	0.370	84	8,500	25
	F30T9 EX-N	30	EX-N	5,000	850	2,500	36	893	T9	28	G13	0.370	84	8,500	25
	F30T9/EX-L	30	EX-L	3,000	830	2,500	36	893	T9	28	G13	0.370	84	8,500	25
	FL40SS/EDK	37	EX-D-V	7,400	874	3,350	48	1,198	T9	28	G13	0.410	84	12,000	25
	FL40SS/ENK	37	EX-N-V	5,500	850	3,560	48	1,198	T9	28	G13	0.410	84	12,000	25
	FL40SS/ELK	37	EX-L-V	3,000	830	3,560	48	1,198	T9	28	G13	0.410	84	12,000	25
	F40T9/EX-D	37	EX-D	6,700	867	3,350	48	1,198	T9	28	G13	0.420	84	12,000	25
	F40T9 EX-N	37	EX-N	5,000	850	3,560	48	1,198	T9	28	G13	0.420	84	12,000	25
	F40T9 EX-CW	37	EX-CW	4,200	842	3,560	48	1,198	T9	28	G13	0.420	84	12,000	25
F40T9/EX-L	37	EX-L	3,000	830	3,560	48	1,198	T9	28	G13	0.420	84	12,000	25	
Rapid Start Type (No Starter Used)	F40T10/EX-50/RS	40	EX-N	5,000	850	3,450	48	1,198	T10	32	G13	0.420	84	12,000	25
	F40T10/EX-41/RS	40	EX-CW	4,200	842	3,450	48	1,198	T10	32	G13	0.420	84	12,000	25
	F40T10/EX-35/RS	40	EX-W	3,500	835	3,450	48	1,198	T10	32	G13	0.420	84	12,000	25
	FLR110H-EX-D/A	110	EX-D	6,700	867	9,200	96	2,367	T12	38	R17d	0.800	84	12,000	10
Halophosphor															
Preheat Start Type	F4T5/D	4	Daylight	6,500	—	120	6	135	T5	15.5	G5	0.170	74	8,000	50
	F4T5/CW	4	Cool White	4,200	—	135	6	135	T5	15.5	G5	0.170	61	8,000	50
	F4T5/W	4	White	3,500	—	135	6	135	T5	15.5	G5	0.170	60	8,000	50
	F4T5/WW	4	Warm White	3,000	—	135	6	135	T5	15.5	G5	0.170	53	8,000	50
	F6T5/D	6	Daylight	6,500	—	250	9	211	T5	15.5	G5	0.160	74	10,000	50
	F6T5/CW	6	Cool White	4,200	—	300	9	211	T5	15.5	G5	0.160	61	10,000	50
	F6T5/W	6	White	3,500	—	300	9	211	T5	15.5	G5	0.160	60	10,000	50
	F6T5/WW	6	Warm White	3,000	—	300	9	211	T5	15.5	G5	0.160	53	10,000	50
	F8T5/D	8	Daylight	6,500	—	330	12	287	T5	15.5	G5	0.145	74	10,000	50
	F8T5/CW	8	Cool White	4,200	—	400	12	287	T5	15.5	G5	0.145	61	10,000	50
	F8T5/W	8	White	3,500	—	400	12	287	T5	15.5	G5	0.145	60	10,000	50
	F8T5/WW	8	Warm White	3,000	—	400	12	287	T5	15.5	G5	0.145	53	10,000	50
	F13T5/D*	13	Daylight	6,500	—	720	21	523	T5	15.5	G5	0.165	74	10,000	50
	F13T5/W*	13	White	3,500	—	820	21	523	T5	15.5	G5	0.165	61	10,000	50
	F13T5/CW*	13	Cool White	4,200	—	820	21	523	T5	15.5	G5	0.165	60	10,000	50
	F13T5/WW*	13	Warm White	3,000	—	820	21	523	T5	15.5	G5	0.165	53	10,000	50
	F10T8/D	10	Daylight	6,500	—	420	13	330	T8	25.5	G13	0.230	74	6,000	25
	F10T8/CW	10	Cool White	4,200	—	490	13	330	T8	25.5	G13	0.230	61	6,000	25
	F10T8/WW	10	Warm White	3,000	—	490	13	330	T8	25.5	G13	0.230	53	6,000	25
	F15T8/D	15	Daylight	6,500	—	770	18	436	T8	25.5	G13	0.300	74	6,000	25
	F15T8/CW	15	Cool White	4,200	—	860	18	436	T8	25.5	G13	0.300	61	6,000	25
	F15T8/WW	15	Warm White	3,000	—	860	18	436	T8	25.5	G13	0.300	53	6,000	25
	F20T8/D	18	Daylight	6,500	—	1,050	24	589	T8	25.5	G13	0.370	74	8,500	25
	F20T8/CW	18	Cool White	4,200	—	1,225	24	589	T8	25.5	G13	0.370	61	8,500	25
	F20T8/WW	18	Warm White	3,000	—	1,225	24	589	T8	25.5	G13	0.370	53	8,500	25
	F30T8/D	28	Daylight	6,500	—	1,800	36	893	T8	25.5	G13	0.390	74	8,500	25
	F30T8/CW	28	Cool White	4,200	—	2,200	36	893	T8	25.5	G13	0.390	61	8,500	25
	F30T8/WW	28	Warm White	3,000	—	2,200	36	893	T8	25.5	G13	0.390	53	8,500	25
	F40T8/D	36	Daylight	6,500	—	2,550	48	1,198	T8	25.5	G13	0.430	74	12,000	25
	F40T8/CW	36	Cool White	4,200	—	3,000	48	1,198	T8	25.5	G13	0.430	61	12,000	25
	F40T8/WW	36	Warm White	3,000	—	3,000	48	1,198	T8	25.5	G13	0.430	53	12,000	25

* F13T5 : The values are under consideration. It is not a final decision value.