



Assembly accessories for application of assembled busbar enclosures.

Technical characteristics

- Busbar supports and end caps are provided with sealings and are supplied including fixing material.
- For type S, the bushing for the (PE)N bar is the same size as the phase bar.



1021487

End caps

Type R 430

- Also suitable for guiding-through of 4 auxiliary bars 6 mm square.

Description	Phase busbars L1, L2, L3	(PE)N	PE earth bar	Type	QPC	Eaton list number
End cap	15 x 4 mm	15 x 4 mm	15 x 3 mm	R 430/4	1	1021487
End cap	15 x 8 mm	15 x 4 mm	15 x 4 mm	R 430/8	1	1021488
End cap	15 x 16 mm	15 x 8 mm	15 x 6 mm	R 430/16	1	1021489
End cap	15 x 24 mm	15 x 12 mm	15 x 6 mm	R 430/24	1	1021490
End cap	15 x 8 mm	15 x 8 mm	15 x 4 mm	R 430/8S	1	1021479
End cap	15 x 16 mm	15 x 16 mm	15 x 6 mm	R 430/16S	1	1021480
End cap	15 x 24 mm	15 x 24 mm	15 x 6 mm	R 430/24S	1	1021481



1860737

End caps and busbar supports

Type UR 403

- For sealing busbar enclosures at both ends of the installation.

Description	Phase busbars L1, L2, L3	(PE)N	PE earth bar	Type	QPC	Eaton list number
End cap and busbar support	15 x 4 mm	15 x 4 mm	15 x 3 mm	UR 403/4	1	1860736
End cap and busbar support	15 x 8 mm	15 x 4 mm	15 x 4 mm	UR 403/8	1	1860737
End cap and busbar support	15 x 16 mm	15 x 8 mm	15 x 6 mm	UR 403/16	1	1860738
End cap and busbar support	15 x 24 mm	15 x 12 mm	15 x 6 mm	UR 403/24	1	1860739
End cap and busbar support	15 x 8 mm	15 x 8 mm	15 x 4 mm	UR 403/8S	1	1860741
End cap and busbar support	15 x 16 mm	15 x 16 mm	15 x 6 mm	UR 403/16S	1	1860742
End cap and busbar support	15 x 24 mm	15 x 24 mm	15 x 6 mm	UR 403/24S	1	1860743



1933310

Copper busbars, nickel-plated

Description	Dimension (metre)	QPC	Eaton list number
Nickel-plated copper busbars, for main busbar	15 x 3 (x 1000 mm)	4	1933310*
Nickel-plated copper busbars, for main busbar	15 x 4 (x 1000 mm)	4	1933322*
Nickel-plated copper busbars, for main busbar	15 x 6 (x 1000 mm)	4	1933323*
Nickel-plated copper busbars, for main busbar	15 x 8 (x 1000 mm)	4	1933324*
Nickel-plated copper busbars, for main busbar	15 x 16 (x 1000 mm)	4	1933328*
Nickel-plated copper busbars, for branche connection	20 x 3 (x 1000 mm)	4	1933309*
Nickel-plated copper busbars, for branche connection	25 x 6 (x 1000 mm)	4	1933304*
Nickel-plated copper busbars, for branche connection	30 x 4 (x 1000 mm)	4	1933325*

*) Minimum order length is 4 meter (length 1 m x QPC 4 = 4 m), which is provided as one piece in whole.
Price presented is price per meter.