







plugs & sockets - P17 Tempra

16 to 125 A

| | | | | | | | | | | |
|---|-------------|-------------|---|----------|---|----------|---|----------|---|----------|
| <ul style="list-style-type: none"> • Conforming to IEC 60309-1/60309-2 • Material : Plastic • Self-extinguishing : 850°C • IK 09 according to IEC 62262 | | |  | |  | |  | |  | |
| | | | Surface mounting sockets ↕ | | Panel mounting sockets - inclined | | Mobile sockets | | Straight Plugs | |
| | | | IP 67 | | IP 67 | | IP 67 | | IP 67 | |
| | | | LV | Cat nos. | Pack | Cat nos. | Pack | Cat nos. | Pack | Cat nos. |
| 200 to 250 V ~ 50/60 Hz | 16 A / 20 A | 2 P + ⊥ | 0553 03 | - | 0576 51 | 5/50 | - | - | 0563 03 | 5/20 |
| | 32 A | 2 P + ⊥ | 0553 23 | - | 0576 52 | 5/25 | - | - | 0563 23 | 5/20 |
| 380 to 415 V ~ 50/60 Hz | 32 A | 3 P + ⊥ | 0553 07 | - | 0576 58 | 5/25 | - | - | 0563 27 | 5/20 |
| | | 3 P + N + ⊥ | - | - | 0576 64 | 5/25 | - | - | 0563 28 | 5/20 |
| | 63 A | 3 P + N + ⊥ | 0587 45 | 2 | 0587 25 | 2 | 0587 15 | 2 | 0587 05 | 2 |
| | 125 A | 3 P + N + ⊥ | 0591 07 | 1 | 0591 17 | 1 | 0591 37 | 1 | 0591 27 | 1 |
| ↕ - With isometric threaded cable entries : 16 A = M 20, 32 A = M 25, 63 A = M 32. | | | | | | | | | | |

plugs & sockets - Hypra

16 to 125 A

| | | | | | | | | | | |
|---|-------------|-------------|---|----------|---|----------|---|----------|---|----------|
| <ul style="list-style-type: none"> • Conforming to IEC 60309-1/60309-2 • Material : Plastic • IK 09 according to IEC 62262 | | |  | |  | |  | |  | |
| | | | Prisinter panel mounting sockets | | Panel mounting sockets | | Mobile sockets | | Straight plugs | |
| | | | IP 44 | | IP 44 | | IP 44 | | IP 44 | |
| | | | LV | Cat nos. | Pack | Cat nos. | Pack | Cat nos. | Pack | Cat nos. |
| 200 to 250 V ~ 50/60 Hz | 16 A / 20 A | 2 P + ⊥ | 0520 02 | 1/10 | - | - | - | - | 0520 42 | - |
| | 32 A | 2 P + ⊥ | 0527 02 | 1/6 | - | - | - | - | 0527 42 | - |
| 380 to 415 V ~ 50/60 Hz | 16 A / 20 A | 3 P + ⊥ | - | - | 0522 23 | 5/50 | 0522 83 | 5/50 | 0522 43 | 5/50 |
| | | 3 P + ⊥ | 0529 03 | 1/6 | - | - | - | - | 0529 43 | - |
| | 32 A | 3 P + N + ⊥ | 0529 04 | 1/6 | - | - | - | - | 0529 44 | 5/15 |
| | | 3 P + ⊥ | - | - | 0538 23 | 1 | - | - | 0538 43 | 1/5 |
| | 63 A | 3 P + N + ⊥ | 0536 04 | 1 | - | - | - | - | 0538 44 | 1/5 |
| 125 A | 3 P + N + ⊥ | - | - | - | - | - | - | - | - | |
| * In IEC 38, the network voltage value of 230/400 V AC has been standardised. This value should progressively supercede the values of 220/380 V AC and 240/415 V AC. Wherever there is a reference to 230 V or 400 V, they may be read as 220 V or 240 V and 380 V or 415 V respectively. | | | | | | | | | | |