

[TopPage](#)>>[Search Result](#)>>51205

Thrust Ball Bearings

Bearing No. : **NACHI 51205**

■ **Bearing Type** Flat back face ▾

■ **Clearance** ▾

■ **Tolerance Class** Normal Class ▾

<p>Dimensions</p> <p>d = 25 0 -0.010</p> <p>D = 47 0 -0.016</p> <p>T = 15 0 -0.075</p> <p>r = 0.6~1.5 (Radial Direction and Axial Direction)</p> <p>D1(min) = 27 d1(max) = 47</p>			<p>Dimensions</p> <p>da(min) = 38 Da1(max) = 34 ra(max) = 0.6 Mass = 0.12 kg</p>																
<p>Basic Dynamic Load Rating Ca : 27,800 N</p> <p>Basic Static Load Rating Coa : 50,500 N</p> <p>Limiting Speed ;</p> <p> Grease Lubrication : 3,700 min⁻¹</p> <p> Oil Lubrication : 5,600 min⁻¹</p>	<table border="1"> <thead> <tr> <th></th> <th>INNER RING</th> <th>OUTER RING</th> </tr> </thead> <tbody> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td>-</td> </tr> <tr> <td> Axial Runout with Bore :</td> <td>-</td> <td></td> </tr> <tr> <td> Axial Runout with Raceway :</td> <td>-</td> <td>-</td> </tr> <tr> <td> Width Variation :</td> <td>-</td> <td>-</td> </tr> <tr> <td> Radial Runout :</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-	-	Width Variation :	-	-	Radial Runout :	-	-
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-	-																	
Width Variation :	-	-																	
Radial Runout :	-	-																	

[Back](#)

[Calc](#)

[DXF](#)

[Print](#)