

[TopPage](#)>>[Search Result](#)>>H715345/H715311

# Tapered Roller Bearings

Bearing No. : **NACHI**  
**H715345/H715311**

■ Bearing Type 
■ Clearance 
■ Tolerance Class

<p>Dimensions</p> <p>d = 71.438 <sup>+0.013</sup><sub>0</sub></p> <p>D = 136.525 <sup>+0.025</sup><sub>0</sub></p> <p>T = 46.038 <sup>+0.203</sup><sub>0</sub></p> <p>B = 46.038</p> <p>C = 36.513</p> <p>r1(min) = 3.6~ (Radial Direction)</p> <p>r1(min) = 3.6~ (Axial Direction)</p> <p>r2(min) = 3.2~ (Radial Direction)</p> <p>r2(min) = 3.2~ (Axial Direction)</p> <p>a = 9</p>		<p>Dimensions</p> <p>da(min) = 93</p> <p>db(max) = 87</p> <p>Da(min) = 118</p> <p>Db(min) = 132</p> <p>r1a(max) = 3.6</p> <p>r2a(max) = 3.2</p> <p>Mass(Cone) = 2.15 kg</p> <p>Mass(Cup) = 0.95 kg</p>																							
<table border="0"> <tr> <td>Basic Dynamic Load Rating Cr :</td> <td><b>231,000</b> N</td> <td>INNER RING</td> <td>OUTER RING</td> </tr> <tr> <td>Basic Static Load Rating Cor :</td> <td><b>369,000</b> N</td> <td>O.D.Surface Runout with Side :</td> <td>-</td> </tr> <tr> <td>Limiting Speed ;</td> <td></td> <td>Axial Runout with Bore :</td> <td>-</td> </tr> <tr> <td>Grease Lubrication :</td> <td><b>2,800</b> min<sup>-1</sup></td> <td>Axial Runout with Raceway :</td> <td>-</td> </tr> <tr> <td>Oil Lubrication :</td> <td><b>3,700</b> min<sup>-1</sup></td> <td>Width Variation :</td> <td>-</td> </tr> <tr> <td></td> <td></td> <td>Radial Runout :</td> <td><b>0.051</b>      <b>0.051</b></td> </tr> </table>		Basic Dynamic Load Rating Cr :	<b>231,000</b> N	INNER RING	OUTER RING	Basic Static Load Rating Cor :	<b>369,000</b> N	O.D.Surface Runout with Side :	-	Limiting Speed ;		Axial Runout with Bore :	-	Grease Lubrication :	<b>2,800</b> min <sup>-1</sup>	Axial Runout with Raceway :	-	Oil Lubrication :	<b>3,700</b> min <sup>-1</sup>	Width Variation :	-			Radial Runout :	<b>0.051</b> <b>0.051</b>
Basic Dynamic Load Rating Cr :	<b>231,000</b> N	INNER RING	OUTER RING																						
Basic Static Load Rating Cor :	<b>369,000</b> N	O.D.Surface Runout with Side :	-																						
Limiting Speed ;		Axial Runout with Bore :	-																						
Grease Lubrication :	<b>2,800</b> min <sup>-1</sup>	Axial Runout with Raceway :	-																						
Oil Lubrication :	<b>3,700</b> min <sup>-1</sup>	Width Variation :	-																						
		Radial Runout :	<b>0.051</b> <b>0.051</b>																						

⏪ Back
➤ Calc
➤ DXF
🖨 Print