



Outlet flange allowable external force

Axis	Allowable external force (N)
X	1610
Y	1610
Z	1610

SIZE	SEY THROAT DIA. ds	LIFT DIA. dt	INLET NECK A	B	OUTLET FLANGE (ASME) D1	T1	f1	g1	C1	M1	h1	Rc	Rd	DRAIN HOLE SIZE	THREAD SIZE	CENTER TO FACE	L	H1	H	WEIGHT	REMARKS
3-M2-8	66	57.4	14.4	184	282	55	381	42	1.6	270	330	12	25	3/4	1	270	325	1720	980kg		

NO.	ITEM	MATERIAL	REMARKS
52	SUPPORT	2 SS400	
51	NUTS	12 SA194-2H	
50	WEATHER HOOD	1 SS400	
49	EYE BOLTS	2 SS400	
48	ADJ. BUSH	1 SUS403	
47	CONED DISC SPRING	2 SUS630	
46	HEX SOCKET SET SCREW	1 SUS304	
45	EXHAUST PIPE	2 Sets SUS304-TP, SUSF304	
44	TEST GAG	1 SS400	
43	GAG PLUG	1 SS400	
42	FLAT HEAD BOLTS	2 SUS304	
41	HEX SOCKET HEAD CAP SCREWS	2 SUS304-A2	
40	SLIT PIN	3 SUS304	
39	DRAIN PLUG	1 SUS304	
38	FORK LEVER PIN	1 SS400	
37	EASING LEVER PIN	1 SS400	
36	LOCK PLATE	1 SUS304	
35	FLOATING WASHER	1 B564-NO4400	
34	STUD BOLT & NUT	12 SA193-B7, SA194-2H	
33	STUD BOLT & NUT	8 SA193-B7, SA194-2H	
32	FORK LEVER	1 FCWB31-08	
31	EASING LEVER	1 SS400	
30	CAP	1 FGD450-10	
29	LOCK NUT	1 S45C	
28	LIFTING WASHER	1 SS400	
27	ADJ. SCREW LOCK NUT	1 SUS304	
26	ADJUSTING SCREW	1 SUS420J2	
25	THRUST BEARING	1 PURPHASE	
24	SPRING	1 SUS10	
23	UPPER SPRING WASHER	1 SUS403	
22	LOWER SPRING WASHER	1 SUS403	
21	STEP RING	1 SUS420J2	
20	BONNET	1 SAZ17M-WC8	
19	CENTER THROTTLE	1 SUS630	
18	SPINDLE GUIDE	1 B665-NO5600	
17	LIFT STOPPER	1 SUS420J2	
16	ORIFICE PIECE	1 SUS304	
15	COOLING SPOOL	1 SAZ17M-WC8	
14	UPPER LOCK BOLT	1 SUS431	
13	LOWER LOCK BOLT	1 SUS431	
12	UPPER RING	1 SUS420J2	
11	LOWER RING	1 SUS420J2	
10	GUIDE	1 SUS420J2	
9	SPINDLE	1 S1110NLOY A2	
8	BODY	1 SAZ17M-WC8	
7	DISC HOLDER	1 SUS420J2	
6	DISC COLLAR	1 SUS630	
5	DISC CENTER	1 B637-NO7750	
4	NOZZLE	1 SA182M-F12	
3			
2			
1			

TYPE SL1053-C2-H1 (T)

TAG NO. 50/60HMH01AA701/703/705/707/711/713/715/717

DWG. NO. 2018H 0183-0190, 0216-0223-01-2

MFG NO. 810183-810190, 810216-810223

FUKUI SEISAKUSHO CO., LTD.