

02 NaClO UNLOADING PUMP MOTOR DATA SHEET

1. Name of motor	-	NaClO unloading pump motor
2. Manufacturer	-	SIEMENS
3. Country of origin	-	CHINA
4. Type/machine code	-	1LE0003-OEA42-1JA4-Z W88 2.2KW
5. Applied standard (characteristics)	-	IEC
6. Ratings		
(1) Rated output	kW	2.2
(2) Service factor	-	1.0
(3) Number of pole	-	2
(4) Rated speed	R.min ⁻¹	2910
(5) Rated voltage	V	380
(6) Number of phases	-	3
(7) Rated frequency	Hz	50
(8) Insulation class	-	F
(9) Temperature rise	-	B
(10) Rated duty		S1
7. Service Conditions		
(1) Starting method	-	Directly
(2) Direction of rotation (viewed from DE)	-	CW or CCW
(3) Reverse rotation (Yes / No)	-	No
(4) Location (Indoor / Outdoor)		Outdoor
(5) Enclosure IP rating	-	
(a) Motor frame	-	IP55
(b) Terminal boxes	-	IP55
(6) Installation (Horizontal / Vertical)		Horizontal
(7) Design ambient temperature	°C	-20 ~ 40
(8) Explosion proof (Required / Not required)		Not required
(9) Noise level (at full-load condition)	dB (A)	55

Originator CHEC WATER	Identification number TJB56-GNA-E-DAS-0001	Rev. B	Date 31/MAR/19	Lang. En	Sheet 7/102
--------------------------	---	-----------	-------------------	-------------	----------------

8. Characteristics		
(1) Current		
(a) Normal current	A	4.4
(b) No-load current	A	1.85
(c) Starting current	A	33
(2) Torque		
(a) Starting torque	%	2.3
(b) Maximum torque	%	3.6
(3) Slip at rated output		0.03
(4) Efficiencies		
(a) At 100% load	%	85.9
(b) At 75% load	%	87.2
(c) At 50% load	%	86.8
(d) At 25% load	%	80.1
(5) Power factor		
(a) At rated load	%	88
(b) At starting load	%	
(6) GD2 coupled with driven equipment	kg-m ²	0.00356
(7) Starting time with driven equipment	s	1-2
(8) Allowable number of starts	-	
(a) From cold condition per hour	-	3
(b) From hot condition per hour	-	2
(c) Minimum time between 2 starts (running state)	min	
(d) Minimum time between 2 starts (stop state)	min	
(9) Allowable locked-rotor time		NA
(a) At cold condition	s	
(b) At hot condition	s	
9. Constructions		
(1) Stator winding connection (Wye / Delta)	-	Wye

Originator CHEC WATER	Identification number TJB56-GNA-E-DAS-0001	Rev. B	Date 31/MAR/19	Lang. En	Sheet 8/102
--------------------------	---	-----------	-------------------	-------------	----------------

(2) Type of bearing (DE / NDE)	-	6205 2Z C3
(3) Lubricants		
(a) Recommended lubricant and brand name	-	
(b) Pouring method	-	
(c) Quantity of lubricant for initial filling	-	
(d) Recommended interval for recharging	-	
(e) Recharging quantity	-	
(f) Location of pouring	-	
(indicated in the outline drawing)		
(4) Bearing cooling water requirement (if required)		
(a) Quantity	m ³ /h	NA
(b) Inlet water temperature	°C	NA
(c) Required cooling water pressure	kPa	NA
(d) Type of cooling water	-	NA
(5) Water to air heat exchanger (if applied)		
(a) Quantity of cooling water	m ³ /h	NA
(b) Inlet water temperature	°C	NA
(c) Required cooling water pressure	kPa	NA
(d) Type of cooling water	-	NA
(6) Space heater (AC 220V 1 phase)	W	NA
(7) Weight	kg	39
10. Attached document numbers		
(1) Motor outline drawing	-	NA
(2) Terminal box drawings	-	NA
(a) For main power	-	NA
(b) For instruments	-	NA
(c) For space heater	-	NA
(3) Current transformers (for MV motors only)		NA
(a) Characteristics curves	-	NA

Originator CHEC WATER	Identification number TJB56-GNA-E-DAS-0001	Rev. B	Date 31/MAR/19	Lang. En	Sheet 9/102
--------------------------	---	-----------	-------------------	-------------	----------------

(b) Outline drawing	-	NA
(4) Efficiency curves	-	NA
(5) Thermal capability curves		NA
(a) At cold condition	-	NA
(b) At hot condition	-	NA
(6) Starting and speed torque characteristics at 80%, 90% and 100% voltage	-	NA

CONFIDENTIAL

Originator CHEC WATER	Identification number TJB56-GNA-E-DAS-0001	Rev. B	Date 31/MAR/19	Lang. En	Sheet 10/102
--------------------------	---	-----------	-------------------	-------------	-----------------