Select Fully Formulated Coolant

Fleetguard's heavy duty coolant products use propylene glycol which is a non-poisonous, biodegradable, environmentally friendly and safer alternative to ethylene glycol based coolants. Fleetguard offer two technologies to cover your needs: PGPlus (hybrid technology, dual buffer with nitrite/molybdate cavitation protection) and PG Platinum (extended life OAT technology that is nitrite free and has minimal maintenance requirements).

COOLANT

20



PG Platinum®

- Organic lifetime propylene glycol premixed coolant with 6 years, 1.5 million kms, 36,000 hours service life
- For use in all heavy duty, light duty and gas engines
- Protects against liner pitting and provides solid corrosion protection for aluminum, cast iron, copper, brass, and solder
- No SCA or extenders needed for life of the coolant
- Easy maintenance with extended service non-chemical filters
- Contains proprietary scale inhibitors
- Compatible with gaskets, elastomers, non-metallics including silicon seals/hoses
- OEM approved formulation free of nitrite, amine, phosphate, borate, silicate, and 2-ethylhexonic acid
- Approved by Cummins to CES14603, CES14439 (for heavy duty) & CES 14636 (for light duty)
- Meets ASTM D3306, ASTM D6210 and TMC RP 330

	PG Platinum Premix
4L Bottle (1 Gal.)	CC36082
10L Drum (2.6 Gal.)	CC36083
20L Drum (5.3 Gal.)	CC36084
208L Drum (55 Gal.)	CC36085
1000L Pallecon (263 Gal.)	CC36086
Bulk (20,000L)	CC36087



PGPlus[®]

- Fully formulated hybrid propylene glycol based premixed coolant with dual borate, phosphate buffer and low silicate formulation for use in all heavy duty diesel and gas engines
- Life-of-the-engine coolant, with 5 years, 1 million kms, 20,000 hours service life
- Protects against liner pitting and provides solid corrosion protection for aluminum, cast iron, copper, brass, and solder
- Contains proprietary scale inhibitors
- Compatible with Fleetguard DCA4 liquid, or DCA4+ chemical filters
- Approved by Cummins to CES14603 and CES14439 (for heavy duty)
- Meets ASTM D3306, ASTM D6210, TMC RP 330

	PGPlus Premix	PGPlus Concentrate
4L Bottle (1 Gal.)	CC2870	CC2657
10L Drum (2.6 Gal.)	CC2871	
20L Drum (5.3 Gal.)	CC2869	CC2658
208L Drum (55 Gal.)	CC2868	CC2659
1000L Pallecon (263 Gal.)	CC2867	CC2832
Bulk (20,000L)	CC2866	