

Unit : mm

Thickness d_2 standard dimensions and tolerance		1.80±0.08	2.65±0.09	3.55±0.10	5.30±0.13	7.00±0.15
Symbol		A	B	C	D	E
f		0.1 or less	0.12 or less	0.14 or less	0.16 or less	0.18 or less
Inner diameter d_1		Bearing number				
Standard dimensions	Tolerance					
18.0	±0.21		B0180G	C0180G		
19.0	±0.22		B0190G	C0190G		
20.0	±0.22		B0200G	C0200G		
21.2	±0.23		B0212G	C0212G		
22.4	±0.24		B0224G	C0224G		
23.6	±0.24		B0236G	C0236G		
25.0	±0.25		B0250G	C0250G		
25.8	±0.26		B0258G	C0258G		
26.5	±0.26		B0265G	C0265G		
28.0	±0.28		B0280G	C0280G		
30.0	±0.29		B0300G	C0300G		
31.5	±0.31		B0315G	C0315G		
32.5	±0.32		B0325G	C0325G		
33.5	±0.32		B0335G	C0335G		
34.5	±0.33		B0345G	C0345G		
35.5	±0.34		B0355G	C0355G		
36.5	±0.35		B0365G	C0365G		
37.5	±0.36		B0375G	C0375G		
38.7	±0.37		B0387G	C0387G		
40.0	±0.38			C0400G	D0400G	
41.2	±0.39			C0412G	D0412G	
42.5	±0.40			C0425G	D0425G	
43.7	±0.41			C0437G	D0437G	
45.0	±0.42			C0450G	D0450G	
46.2	±0.43			C0462G	D0462G	
47.5	±0.44			C0475G	D0475G	
48.7	±0.45			C0487G	D0487G	
50.0	±0.46			C0500G	D0500G	
51.5	±0.47			C0515G	D0515G	
53.0	±0.48			C0530G	D0530G	
54.5	±0.50			C0545G	D0545G	
56.0	±0.51			C0560G	D0560G	
58.0	±0.52			C0580G	D0580G	
60.0	±0.54			C0600G	D0600G	
61.5	±0.55			C0615G	D0615G	
63.0	±0.56			C0630G	D0630G	
65.0	±0.58			C0650G	D0650G	
67.0	±0.59			C0670G	D0670G	
69.0	±0.61			C0690G	D0690G	
71.0	±0.63			C0710G	D0710G	
73.0	±0.64			C0730G	D0730G	
75.0	±0.66			C0750G	D0750G	
77.5	±0.67			C0775G	D0775G	
80.0	±0.69			C0800G	D0800G	
82.5	±0.71			C0825G	D0825G	
85.0	±0.73			C0850G	D0850G	
87.5	±0.75			C0875G	D0875G	
90.0	±0.77			C0900G	D0900G	