


### POLICLEAN™ Mounted Tools




For general-purpose peripheral grinding.

#### Recommendation for Use

These tools can be used on flexible shaft drives or straight grinders (electrical or air-powered).

**PFERD Specification Number**  
PCLZY

Diameter (D) x Length [L] [Inches]	Shank Dia. [Inches]	EDP Number	Recom. Speed RPM	Max. RPM	
2 x 1/2	1/4	44810	6,000 - 7,000	15,000	5
2 x 1	1/4	44811	6,000 - 7,000	15,000	5
3 x 1/2	1/4	44812	4,000 - 5,100	10,000	5
3 x 1	1/4	44813	4,000 - 5,100	10,000	5
4 x 1/2	1/4	44814	3,000 - 3,800	7,500	5

### POLICLEAN™ Discs



The non-woven cleaning fabric is supported by a backing pad. This design allows POLICLEAN™ discs to be used very effective in face grinding.


#### Recommendation for Use

Preferably for use on slow-running angle grinders.

**Recommended Peripheral Speed**  
6,000 - 8,000 SFPM.

**PFERD Specification Number**  
PCLD



Diameter x Thickness [Inches]	Arbor Hole/ Thread Size [Inches]	EDP Number	Recom. Speed RPM	Max. RPM	
<b>Plain Arbor Hole</b>					
4-1/2 x 1/2	7/8	44862	5,000 - 7,000	10,000	5
5 x 1/2	7/8	44863	5,000 - 7,000	10,000	5
<b>Threaded Hub</b>					
4-1/2 x 1/2	5/8-11	44867	5,000 - 7,000	10,000	5
5 x 1/2	5/8-11	44868	5,000 - 7,000	10,000	5