

P 17 Tempra IP 67 - 63 A & 125A

Plug dan soket industri



587 24



587 05



587 14

Terminal connection: 63 A

Soket: max. 1 x 25 mm² rigid

Plug and mobile soket: max. 1 x 16 mm² flexible 125 A

Soket: max. 1 x 70 mm² rigid

Plug and mobile soket: max. 1 x 50 mm² flexible

IK 09 sesuai dengan IEC/EN 62262

Bahan: plastic

Padam sendiri : 850 °C

Ketahanan suhu: - 50 °C to + 100 °C

Sesuai dengan standar IEC 60309-1-2

Pak	No. Kat.	IP 67 - 63A
		Panel mounting socket
		 200/250V
2	587 20	2P + E
		 380/415V
2	587 24	3P + E
2	587 25	3P + N + E

		Surface mounting socket
		 200/250V
2	587 40	2P + E
		 380/415V
2	587 44	3P + E
2	587 45	3P + N + E

		Plug
		 200/250V
2	587 00	2P + E
		 380/415V
2	587 04	3P + E
2	587 05	3P + N + E

		Mobile socket
		 200/250V
2	587 10	2P + E
		 380/415V
2	587 14	3P + E
2	587 15	3P + N + E

Pak	No. Kat.	IP 67 - 125A
		Panel mounting socket
		 380/415 V
1	591 16	3 P + E
1	591 17	3 P + N + E
		Surface mounting socket
		 380/415 V
1	591 06	3 P + E
1	591 07	3 P + N + E

		Plug
		 380/415 V
1	591 26	3 P + E
1	591 27	3 P + N + E

		Mobile socket
		 380/415 V
1	591 36	3 P + E
1	591 37	3 P + N + E